

UNCLASSIFIED

AD NUMBER
AD022941
CLASSIFICATION CHANGES
TO: unclassified
FROM: confidential
LIMITATION CHANGES
TO: Approved for public release, distribution unlimited
FROM: Distribution authorized to DoD only; Administrative/Operational Use; FEB 1953. Other requests shall be referred to Bureau of Aeronautics [Navy], Washington, DC 20350.
AUTHORITY
28 Feb 1965, DoDD 5200.10; USNASC ltr, 6 Apr 1977

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD _____

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200.10



UNCLASSIFIED

Services Technical Information Agency

22941

WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA
D FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED
MINT PROCUREMENT OPERATION. THE U. S. GOVERNMENT THEREBY INCURS
COSTS, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE
MENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE
WINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY
TION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER
OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE,
ELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by

DOCUMENT SERVICE CENTER

WITT BUILDING, DAYTON, 2, OHIO

**NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE
NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING
OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.
THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN
ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.**

SECURITY INFORMATION

AD NO. 22941
ASTIA FILE COPY

BuAer Report AE-61-4

Fundamentals of Design
of Piloted Aircraft
Flight Control Systems

Volume II, Addendum 1

DYNAMICS OF THE AIRFRAME

Reproduction of this document in any form by other than naval activities is not authorized except by special approval of the Secretary of the Navy or the Chief of Naval Operations, as appropriate

This publication shall not be carried in aircraft on combat missions or when there is a reasonable chance of its falling into the hands of an unfriendly nation, unless specifically authorized by the Operational Commander.

PUBLISHED BY DIRECTION OF
THE CHIEF OF THE BUREAU OF AERONAUTICS

NOTICE—This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U. S. C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

FEBRUARY 1953

SECURITY INFORMATION - CONFIDENTIAL

The material of this addendum forms part of Report AE-61-4II, which together with Report AE-61-4I, has been written under BuAer Contract NOas 51-514(c), "Fundamentals of Design of Piloted Aircraft Flight Control Systems." These form part of a series of manuals being written for the purpose of providing a unified approach to problems of control system design.

For the sake of securing as wide a distribution as possible, Report AE-61-4I, "Methods of Analysis and Synthesis," which is Volume I of this series, and the part, "Dynamics of the Airframe" (Vol. II), of AE-61-4II which precedes this confidential addendum, have been issued in an unclassified status, in accordance with one of the general intents of the series to provide a source of information to be used by engineers in bridging the gap between their collegiate training and the more advanced topics of system engineering.

Since the figures of this addendum contain classified data, they could not be included in the body of this Report, but are presented here in order to include the maximum usable information available at this time. Because of the disparity in level of classification, no mention of this addendum has been made in the body of this Report, but the information herein is to be considered in conjunction with the contents of Chapter IV.

The numerical values and the ranges of values of derivatives shown on the following charts are estimates, based on trends shown by flight tests, wind tunnel tests, and theory; they apply only to fighter type piloted aircraft of today and the near future. They do not apply to missile configurations where the wing is quite small compared to the body, for in these configurations the range of values of non-dimensional derivatives can become very large. (Pitkin, Marvin, and Ankenbruck, Herman O. "Estimation of Range of Stability Derivatives for Current and Future Pilotless Aircraft." NACA Research Memorandum, RM L7E29, Langley Memorial Aeronautical Laboratory, Langley Field, Va., October 8, 1947.)

The following notation has been used in the graphs of this portion of this Report:

A solid line (————) has been used for straight wing aircraft; a broken line (— — — —), for swept wing; and a dotted line (-----) for delta wing.

It is to be noted that an abrupt and very large increase in C_D occurs in the transonic region, and that the delta wing configuration reduces this effect. The estimated range of values of C_D for present and near-future jet fighter type aircraft is from 0.01 to 0.50.




Figure A.1 Variation of C_D with Mach Number for Several High Speed Jet Aircraft

It may be seen that C_{D_u} is approximately zero up to the critical Mach number region at which point it rises abruptly to large positive values, but that the abruptness of the rise and the magnitude which C_{D_u} attains are much less for the delta wing configuration. The estimated range of values of C_{D_u} for present and near-future jet fighter type aircraft is from -0.01 to 0.50.




Figure A-2 Variation of C_{D_u} with Mach Number for Several High Speed Jet Aircraft




Figure A-3 Variation of C_{D_α} with Mach Number for Several High Speed Jet Aircraft




Figure A - 4. Variati of Equilibrium Lift Coefficient for Level Flight with Mach Number for Several High Speed Jet Aircraft




Figure A - 5 Variation of C_{L_u} with Mach Number for Several High Speed Jet Aircraft




Figure A - 6 Variation of C_{L_α} with Mach Number for High Speed Jet Aircraft




Figure A-7 Variation of C_{L_α} with Mach Number for Several High Speed Jet Aircraft

The estimated range of values of C_{L_q} for present and near-future jet fighter type aircraft is from 0 to 8.




Figure A-8 Variation of C_{L_q} with Mach Number For Several High Speed Jet Aircraft




Figure A-9 Variation of $C_{L\delta_g}$ with Mach Number for Several High Speed Jet Aircraft




Figure A - 10 Variation of C_{m_u} with Mach Number for Several High Speed Jet Aircraft




Figure A - 11 Variation of $C_{m\alpha}$ with Mach Number for Several High Speed Jet Aircraft

For the XF-92, positive values are attained in the transonic and supersonic region. Although data concerning the performance of the other airplanes in the transonic region are scarce, it is probable that some of these configurations would exhibit positive values also. The estimated range of values of $C_{m\dot{q}}$ for present and near-future jet fighter type for present and near-future jet fighter type aircraft is from -10 to +3.




Figure A - 12 Variation of $C_{m\dot{q}}$ with Mach Number for Several High Speed Jet Aircraft




Figure A-13 Variation of C_{mq} with Mach Number for Several High Speed Jet Aircraft

For all configurations, the elevator becomes much less effective in the transonic region. The estimated range of values of C_{δ_z} for present and near-future jet fighter type aircraft is from 0 to +1.5.




Figure A-14 Variation of C_{δ_z} with Mach Number for Several High Speed Jet Aircraft

Drake concludes that decreasing $C_{y\beta}$ improves the overall flight behavior.

(Drake, H.M., "The Effect of Lateral Area on the Lateral Stability and Control Characteristics of an Airplane as Determined by Tests of a Model in the Langley Free-Flight Tunnel," NACA Advance Restricted Report, ARR L5L05, Langley Memorial Aeronautical Laboratory, Langley Field, Va., February 1946.)

There is no apparent correlation between $C_{y\beta}$ values and wing planform type. The estimated range of values of $C_{y\beta}$ for present and near-future jet fighter type aircraft is from -0.1 to -1.5 .




Figure A - 15 Variation of $C_{y\beta}$ with Mach Number for Several High Speed Jet Aircraft

The estimated range of values of C_{y_r} for present and near-future jet fighter type aircraft is from 0 to 1.2.




Figure A - 16 Variation of C_{y_r} with Mach Number for Several High Speed Jet Aircraft




Figure A-17 Variation of C_{yp} with Mach Number for Several High Speed Jet Aircraft

The estimated range of values of C_{y_R} for present and near-future jet fighter type aircraft is from 0 to +.5.




Figure A-18 Variation of C_{y_R} with Mach Number for Several High Speed Jet Aircraft




Figure A-19 Variation of $C_{n\beta}$ with Mach Number for Several High Speed Jet Aircraft

Although the value of C_{n_r} is rather large for the D-558-II, this airplane exhibits poor Dutch roll damping characteristics; this emphasizes the fact that Dutch roll damping cannot be predicted merely by examining this derivative alone. The estimated range of values of C_{n_r} for present and near-future jet fighter type aircraft is from 0 to -1.0.




Figure A-20 Variation of C_{n_r} with Mach Number for Several High Speed Jet Aircraft

SECURITY INFORMATION - CONFIDENTIAL




Figure A - 21 Variation of C_{np} with Mach Number for Several High Speed Jet Aircraft

CONFIDENTIAL

For all configurations, rudder effectiveness decreases abruptly in the transonic region. The estimated range of values of $C_{n\delta_R}$ for present and near-future jet fighter type aircraft is from 0 to $-.15$.




Figure A-22 Variation of $C_{n\delta_R}$ with Mach Number for Several High Speed Jet Aircraft

The equilibrium lift coefficient has a great effect on this derivative. The estimated range of values of $C_{n_{\delta A}}$ for present and near-future jet fighter type aircraft is from $-.08$ to $+.08$.




Figure A - 23 Variation of $C_{n_{\delta A}}$ with Mach Number for Several High Speed Jet Aircraft

The equilibrium lift coefficient has a great effect on performance, especially for the delta wing configuration, but there is an abrupt decrease in its effect in the transonic range. The estimated range of values of $C_{L\beta}$ for present and near-future jet fighter type aircraft is from $-.30$ to $+.06$.




Figure A-24 Variation of $C_{L\beta}$ with Mach Number for Several High Speed Jet Aircraft

The equilibrium lift coefficient has a great effect on this derivative, an effect caused by the vertical tail contribution. The estimated range of values of C_{L_r} for present and near-future jet fighter type aircraft is from 0 to .4.




Figure A - 25 Variation of C_{L_r} with Mach Number for Several High Speed Jet Aircraft

The trends with Mach Number are seen to be similar to those for C_{l_a} .
The estimated range of values of C_{l_p} for present and near-future jet fighter type aircraft is from $-.1$ to $-.8$.




Figure A - 26 Variation of C_{l_p} with Mach Number for Several High Speed Jet Aircraft




Figure A - 27 Variation of $C_{L_{eq}}$ with Mach Number for Several High Speed Jet Aircraft

CONFIDENTIAL